



ISUZU NMR 250 AMT CREWCAB E5

SMOD		M220NC0
Axle layout		4x2
Control		Forward

MASS		
Permissible body + payload	kg	2910
Tare - total (T)	kg	2590
Tare - front	kg	1780
Tare - rear	kg	810
GVM	kg	5500
V	kg	5500
GCM	kg	8700
D/T	kg	8700
Axle - front GA/GAU	kg	2900
Axle - front A/AU	kg	2300
Axle - rear GA/GAU	kg	5000
Axle - rear A/AU	kg	4360
Litres of fuel tank 1 included in tare	ltrs	15
Tools included in tare	Jack, warning triangle, basic tool kit	
Spare wheel included in tare	Yes	

PERFORMANCE		
Gradeability at V	%	46.98
Gradeability at D/T	%	29.70
Max. geared road speed (Without SLD)	km/h	118 (113)
Max allowable speed (SLD for SA)	km/h	100

MAJOR DIMENSIONS		
OL - Overall length	mm	6020
OW - Overall width	mm	1815
WB - Wheelbase	mm	3345
CA - Cab to bogie/rear axle	mm	1781
CE - Cab to end of chassis	mm	3346
OH - Overall height	mm	2200
FOH - Front overhang	mm	1110
ROH - Rear overhang	mm	1565
EH - Chassis height rear	mm	758
HH - Ground Clearance	mm	210
Chassis width rear	mm	700
Turning radius (curb to curb)	mm	7250
Turning radius (wall to wall)	mm	7950

ENGINE		
Make		ISUZU
Model		4JJ1-TCC
Capacity	cm3	2 999
Layout		Diesel inline 4
Type		Turbocharged Intercooled Common Rail

ENGINE (CONTINUED)		
Power at r/min	kW	91 @ 2800
Torque at r/min	Nm	330 @ 1 600 - 2600
Emissions standard		Euro 5

CLUTCH		
Make		Exedy
Model		300
Type		Single
Diameter	mm	300
Operation		Hydraulic Assisted
Auto Slack Adjuster		Standard

TRANSMISSION		
Make		ISUZU
Model		MY6E (AMT)
Type		6 Speed synchromesh
Shift		Automated Manual
No. of gears forward		6
1st gear ratio		5.979
2nd gear ratio		3.434
3rd gear ratio		2.040
4th gear ratio		1.397
5th gear ratio		1.000
6th gear ratio		0.759
REV		5.701
Transfer case		No
Manual Locking Hubs (4X4)		No
Limited Slip Differential		No
PTO		PTO Ready

DRIVE AXLE		
Make		ISUZU
Model drive axle front		F029
Model drive axle rear		R050
Hypoid		Standard
Final ratio	:1	5.125

SUSPENSION		
Front		Semi-elliptic springs
Rear		Semi-elliptic springs
Shock absorbers		Front and rear
Stabilisers		Front

STEERING		
Operation		Power

BRAKES		
System type		Vacuum + Power Assist
Front		Drums
Rear		Drums
Anti-lock braking system (ABS) with EBD		Standard
Park/emergency system		Drum on Propshaft
Exhaust brake		Standard

ELECTRICAL & FUEL		
Fuel tank 1 capacity	ltrs	75
Fuel tank 2 capacity	ltrs	0

TYRES		
Size and ply rating - front & rear (Tubed - Opt)		-
Size and ply rating - front & rear (Tubeless)		205/75R16C

CAB & EXTRAS		
Type		Crew
Roof		Low
No. of bunks		0
No. of seats (lap rear & centre)		6
Dual Fuel		-
Airconditioning		Optional
Radio/USB		Standard
Speakers		Standard
USB Charger		Standard
Daytime Running Lights (DRL)		Standard
Telematics		Standard
Driver & Far Passenger Airbags		Standard
Central locking		Standard
Electric windows		Standard
Tilt cab		No

Disclaimer: The information contained in this document was accurate at the time of issue in May 2024. Vehicles may differ from images shown. Please contact your ISUZU Dealer to verify information. Ts&Cs apply. E&OE.

www.isuzu.co.za

ISUZU
With you, for the long run